RKL

Ceiling and wall luminaire


RKL 6 4x40 E27 | Art. No. 880440.000.001.6.00



PMMA 650°C

IK02

HB



IP40

Surface-mounted luminaire for (LED) luminaire with E27 base. Round design with opal cover. Suitable for ceiling and wall mounting. Housing made of profiled, white lacquered steel. Domed, textured cover made of UV-resistant polymethyl methacrylate (PMMA). Also available with high-impact cover made of polycarbonate (PC). The cover is securely attached using spring clips. 3-pin push-fit connector with plug-in contact, loop-through possible. 2 cable entries. Approved for indoor use.

Type of installation and area of application
Ceiling mounting, wall mounting, for mounting directly on the ceiling or wall Approved for indoor use only • Basic lighting


Technical specifications	
Art. No.	880440.000.001.6.00
Article name	RKL 6 4x40 E27
Light source	A60
Socket / base	E27
Number of light sources	4
Power, illuminant (max.)	40 W
Dimmable	not dimmable
Mains voltage	230V/50Hz
Voltage type	AC
Luminaire efficiency	80 %
Light optics	Diffuser made of UV-resistant poly-methyl methacrylate (PMMA)
Light distribution	Extensive
Beam angle	120°
Connection type	3-pin push-fit connector with plug-in contact
Housing	Steel housing, white
Cable entry (position)	rear
Ambient operating temperature – max.	25 °C
Testing	
Protection class	SC I
Protection grade	IP40
Shock resistance	IK02
Flammability (UL94)	HB

RKL 6 4x40 E27 | Art. No. 880440.000.001.6.00


Testing	
Glow-wire resistance	PMMA 650°C
CE-compliant	Yes
Mass and weight	
Diameter	600 mm
Height (H)	165 mm
Gross weight (including packaging)	4,6 Kg
Net weight	3,8 Kg
Contents / packaging quantity	1 Piece

RKL 6 4x40 E27 | Art. No. 880440.000.001.6.00


Accessories (optional)



Art. No.	Article name
36055255	Deco-ring RKL 6 white



Art. No.	Article name
36055258	Deco-ring RKL 6 silver



Art. No.	Article name
36055261	Deco-ring RKL 6 blue

The values stated are design values. Unless otherwise stated, the values apply to an ambient temperature of 25°C. Photometric values are subject to a general tolerance of +-10%. The technical contents correspond to the status at the time of printing. Subject to changes and errors.

LTT Leuchten-Technik Tettnang
Hermannstadtstr. 1 | 88069 Tettnang
Tel: +49 7542 5304-0
info@ltt-licht.de | **www.ltt-licht.de**