



PACDT L12 4400-840 30W ETD

Art. No. 68812830.1031i86.000



PMMA 650°C  
IK03  
HB



LED moisture-proof luminaire with diffuser, dimmable. Housing made of flame-retardant, glass-fibre-reinforced polyester (GRP), light grey. Non-ageing, foamed polyurethane (PU) seal. With integrated LED converter. White steel gear tray. The LED modules can be replaced by an authorised specialist. Diffuser made of UV-resistant polymethyl methacrylate (PMMA), opalised. Stainless-steel diffuser closure. Simple ceiling mounting via enclosed multifunctional rapid mounting brackets made of stainless steel (luminaire can be clipped in). Laterally adjustable by up to 60 mm for easy alignment of the luminaire. Luminaire with limited surface temperature – ideal for areas where conductive dust concentrations are expected.

Type of installation and area of application

Ceiling mounting, wall mounting, for mounting directly on the ceiling or wall, With bracket on ceiling or wall (vertical or horizontal), Suspended with mounting bracket and hanger  
for use indoors and in covered outdoor areas

- Basic lighting

Technical specifications

Art. No.	68812830.1031i86.000
Article name	PACDT L12 4400-840 30W ETD
Light source	LED, replaceable by an authorised specialist
Energy efficiency class(es) of the installed light source(s) (A–G)	Module 1: C
Gear	LED converter, replaceable by an authorised specialist
Number of light sources	1
Dimmable	DALI dimmable
Mains voltage	220-240V/50-60Hz
Voltage type	AC/DC
Max. connected load	31 W
Output/power factor	0,90
Luminous efficacy, max. current draw	142 lm/W
Luminous flux, max.	4400 lm
Flicker value (ripple)	<= 2 %
Colour temperature max.	4000 K
Colour rendering index Ra	Ra > 80
Colour tolerance (MacAdam)	3
Life expectancy	60000 h
Lifetime rating	L80/B10
Light optics	Diffuser made of UV-resistant polymethyl methacrylate (PMMA)
Light distribution	Extensive
Beam angle	120°

**Technical specifications**

Unified Glare Rating UGR – max 4H – 8H	27
Connection type	5-pin push-fit connector with plug-in contact
Number of luminaires on circuit breaker B16	22 Piece
Housing	Housing made of flame-retardant, glass-fibre-reinforced polyester (GRP)
Cable entry (position)	front
Halogen-free wiring	true
Ambient operating temperature – min.	-20 °C
Ambient operating temperature – max.	25 °C

**Testing**

Protection class	SC I
Protection grade	IP65
Information about protection grade	The protection grade is only guaranteed at the factory if mounted using the enclosed mounting bracket
Shock resistance	IK03
Flammability (UL94)	HB
Glow-wire resistance	PMMA 650°C
CE-compliant	Yes
D marking	Yes
Certified for the food industry (HACCP)	Yes

**Mass and weight**

Length (L)	1220 mm
Width (B)	90 mm
Height (H)	105 mm
Fixing span (E1)	880 mm
Fixing span (E2) sliding fit, mounting bracket	760 mm
Information about protection grade	The protection grade is only guaranteed at the factory if mounted using the enclosed mounting bracket
Gross weight (including packaging)	1.83 Kg
Net weight	1.54 Kg
Contents / packaging quantity	1 Piece
Pallet unit	120 Piece

PACDT L12 4400-840 30W ETD

Art. No. 68812830.1031i86.000

## Accessories (optional)



Art. No.	Article name
36078001	Wire mesh protection SG 136



Art. No.	Article name
44149022	TRX chain, galvanised



Art. No.	Article name
35960980	Closure KIT, plastic PAC-D



Art. No.	Article name
35962270	TRA KIT TRA Clip Typ PACD - 35962270

The values stated are design values. Unless otherwise stated, the values apply to an ambient temperature of 25°C. Photometric values are subject to a general tolerance of +10%. The technical contents correspond to the status at the time of printing. Subject to changes and errors.

**LTT Leuchten-Technik Tettnang**  
Hermannstadtstr. 1 | 88069 Tettnang  
Tel: +49 7542 5304-0  
info@ltt-licht.de | [www.ltt-licht.de](http://www.ltt-licht.de)

Page: 3 | 3