




Rondo-Lite 360 1000-830 9W ETC | Art. No. 87636009.1081t90.000


























Type of installation and area of application
Ceiling and wall mounting for use indoors and in covered outdoor areas Basic lighting

Technical specifications	
Art. No.	87636009.1081t90.000
Article name	Rondo-Lite 360 1000-830 9W ETC
Light source	LED, replaceable by an authorised specialist
Gear	LED converter, replaceable by an authorised specialist
Number of light sources	1
Dimmable	not dimmable
Mains voltage	220-240V/50-60Hz
Voltage type	AC/DC
Max. connected load	9 W
Output/power factor	0,85
Luminous efficacy, max. current draw	111 lm/W
Luminous flux, max.	1000 lm
Flicker value (ripple)	<= 5%
Colour temperature max.	3000 K
Colour rendering index Ra	Ra > 80
Colour tolerance (MacAdam)	3
Life expectancy	72000 h
Lifetime rating	L80/B10
Light optics	Diffuser made of UV-resistant polymethyl methacrylate (PMMA)
Light distribution	Extensive
Beam angle	120°
Unified Glare Rating UGR - max 4H- 8H	25





Rondo-Lite 360 1000-830 9W ETC | Art. No. 87636009.1081t90.000

Technical specifications	
Connection type	3-pin push-fit connector with plug-in contact
Number of luminaires on circuit breaker B16	37 Piece
Housing	Housing made of flame-retardant polycarbonate (PC)
Cable entry (position)	rear
Ambient operating temperature - min.	-20 °C
Ambient operating temperature – max.	25℃
Testing	
Protection class	SC I
Protection grade	IP65
Shock resistance	IK03
Flammability (UL94)	НВ
Glow-wire resistance	PMMA 650°C
CE-compliant	Yes
Mass and weight	
Diameter	360 mm
Height (H)	90 mm
Gross weight (including packaging)	2,2 Kg
Net weight	2,2 Kg
Contents / packaging quantity	1 Piece





Rondo-Lite 360 1000-830 9W ETC Art. No. 87636009.1081t90.000