
AOT
Surface-mounted luminaire


LEUCHTENTECHNIK TETTNANG

AOT L12 4800/3000-830 42/27W ETC RWO | Art. No. 50327-42.1111c91.000





PMMA 650°C
IK02
HB



IP50

LED surface-mounted luminaire with opal cover in classic design made of acrylic (PMMA). With adjustable light output (Multi-Lumen), pre-set to maximum output upon delivery. Suitable for ceiling and wall mounting. Luminaire base made of white lacquered steel. Foamed plastic profile Built-in unit gear tray/ reflector made of white steel. White polycarbonate (PC) latch closure. 3-pin push-fit connector with plug-in contact, loop-through possible. 2 cable entries. Approved for indoor use.

Type of installation and area of application
Ceiling and wall mounting Approved for indoor use only • Basic lighting

Technical specifications	
Art. No.	50327-42.1111c91.000
Article name	AOT L12 4800/3000-830 42/27W ETC RWO
Light source	LED, replaceable by an authorised specialist
Energy efficiency class(es) of the installed light source(s) (A–G)	Module 1: D
Gear	LED converter, replaceable by an authorised specialist
Number of light sources	1
Dimmable	not dimmable
Mains voltage	220-240V/50-60Hz
Voltage type	AC/DC
Min. connected load	27 W
Max. connected load	42 W
Output/power factor	0,90
Luminous efficacy, min. current draw	111 lm/W
Luminous efficacy, max. current draw	114 lm/W
Luminous flux, min.	3000 lm
Luminous flux, max.	4800 lm
Flicker value (ripple)	<= 5%
Colour temperature max.	3000 K
Colour rendering index Ra	Ra > 80
Colour tolerance (MacAdam)	3
Life expectancy	50000 h
Lifetime rating	L80/B10
Light optics	Diffuser made of UV-resistant poly-methyl methacrylate (PMMA)
Light distribution	Extensive

AOT L12 4800/3000-830 42/27W ETC RWO | Art. No. 50327-42.1111c91.000

Technical specifications	
Beam angle	120°
Unified Glare Rating UGR – max 4H–8H	22
Connection type	3-pin push-fit connector with plug-in contact
Number of luminaires on circuit breaker B16	40 Piece
Housing	Steel housing, white
Cable entry (position)	rear
Ambient operating temperature – min.	-20 °C
Ambient operating temperature – max.	25 °C
Testing	
Protection class	SC I
Protection grade	IP50
Shock resistance	IK02
Flammability (UL94)	HB
Glow-wire resistance	PMMA 650°C
CE-compliant	Yes
Mass and weight	
Length (L)	1260 mm
Width (B)	105 mm
Height (H)	87 mm
Fixing span (E1)	900 mm
Gross weight (including packaging)	2,6 Kg
Net weight	2,3 Kg
Contents / packaging quantity	1 Piece

AOT L12 4800/3000-830 42/27W ETC RWO | Art. No. 50327-42.1111c91.000

Replacement parts



Art. No.	Article name
44970040	Diffuser RWAO 136

The values stated are design values. Unless otherwise stated, the values apply to an ambient temperature of 25°C. Photometric values are subject to a general tolerance of +-10%. The technical contents correspond to the status at the time of printing. Subject to changes and errors.

LTT Leuchten-Technik Tettnang
Hermannstadtstr. 1 | 88069 Tettnang
Tel: +49 7542 5304-0
info@ltt-licht.de | **www.ltt-licht.de**