



RKL 6 4x12 5200-840 47W ETC EB3 | Art. No. 88041247.1081f81.676



PMMA
650°C

IK02

HB



Round LED surface-mounted luminaire with emergency lighting function (single accumulator). Suitable for ceiling and wall mounting. Housing made of profiled, white lacquered steel. Domed, textured cover made of UV-resistant PMMA (acrylic glass), opal. The cover is securely attached using spring clips. 5-pin push-fit connector with plug-in contact, loop-through possible. 2 cable entries.

Type of installation and area of application

- Ceiling and wall mounting
- Approved for indoor use only
- Basic lighting with emergency lighting function

Technical specifications	
Art. No.	88041247.1081f81.676
Article name	RKL 6 4x12 5200-840 47W ETC EB3
Light source	LED, replaceable by an authorised specialist
Energy efficiency class(es) of the installed light source(s) (A-G)	Module 1: C
Gear	LED converter, replaceable by an authorised specialist
Number of light sources	1
Dimmable	not dimmable
Mains voltage	220-240V/50-60Hz
Voltage type	AC
Max. connected load	47 W
Luminous efficacy, max. current draw	111 lm/W
Luminous flux, max.	5200 lm
Colour temperature max.	4000 K
Colour rendering index Ra	Ra > 80
Colour tolerance (MacAdam)	3
Life expectancy	50000 h
Lifetime rating	L80/B10
Light optics	Diffuser made of UV-resistant polymethyl methacrylate (PMMA)
Light distribution	Extensive
Beam angle	120°
Unified Glare Rating UGR – max 4H-8H	25
Connection type	5-pin push-fit connector with plug-in contact

RKL 6 4x12 5200-840 47W ETC EB3 | Art. No. 88041247.1081f81.676

Technical specifications	
Housing	Steel housing, white
Emergency lighting autonomy	3 h
Ambient operating temperature - min.	5 °C
Ambient operating temperature - max.	25 °C
Testing	
Protection class	SC I
Protection grade	IP40
Shock resistance	IK02
Flammability (UL94)	HB
Glow-wire resistance	PMMA 650°C
CE-compliant	Yes
Mass and weight	
Diameter	600 mm
Height (H)	165 mm
Gross weight (including packaging)	4,3 Kg
Net weight	3,4 Kg
Contents / packaging quantity	1 Piece

RKL 6 4x12 5200-840 47W ETC EB3 | Art. No. 88041247.1081f81.676

Accessories (optional)



Art. No.	Article name
36055255	Deco-ring RKL 6 white



Art. No.	Article name
36055258	Deco-ring RKL 6 silver



Art. No.	Article name
36055261	Deco-ring RKL 6 blue

Replacement parts



Art. No.	Article name
45660026	Diffuser RKL 6 II