



Rondo-Lite 260 800-830 10W ET phc | Art. No. 87626010.1061f90.000



PMMA
650°C

IK06

HB



LED universal surface-mounted luminaire IP65, built-in LED modules and LED gear. Polycarbonate (PC) housing, diffuser/cover made from acrylic (PMMA), opal. Cable entry and gland for mains cable on the underside. Internal 3-pin push-fit connector. Approved for indoor or covered outdoor use, for ceiling and wall mounting (see mounting instructions).

Type of installation and area of application

Ceiling and wall mounting
for use indoors and in covered outdoor areas

- Basic lighting

Technical specifications

Art. No.	87626010.1061f90.000
Article name	Rondo-Lite 260 800-830 10W ET phc
Light source	LED, replaceable by an authorised specialist
Energy efficiency class(es) of the installed light source(s) (A-G)	Module 1: C
Gear	LED converter, replaceable by an authorised specialist
Number of light sources	1
Dimmable	not dimmable
Mains voltage	220-240V/50-60Hz
Voltage type	AC
Max. connected load	10 W
Output/power factor	0,90
Luminous efficacy, max. current draw	80 lm/W
Luminous flux, max.	800 lm
Flicker value (ripple)	<= 30%
Colour temperature max.	3000 K
Colour rendering index Ra	Ra > 80
Colour tolerance (MacAdam)	3
Life expectancy	50000 h
Lifetime rating	L80/B10
Light optics	Diffuser made of UV-resistant poly-methyl methacrylate (PMMA)
Light distribution	Extensive
Beam angle	120°

Rondo-Lite 260 800-830 10W ET phc | Art. No. 87626010.1061f90.000

Technical specifications	
Unified Glare Rating UGR – max 4H-8H	25
Connection type	3-pin push-fit connector with plug-in contact
Number of luminaires on circuit breaker B16	80 Piece
Housing	Housing made of flame-retardant polycarbonate (PC)
Cable entry (position)	rear
Ambient operating temperature – min.	-20 °C
Ambient operating temperature – max.	25 °C
Testing	
Protection class	SC I
Protection grade	IP65
Shock resistance	IK06
Flammability (UL94)	HB
Glow-wire resistance	PMMA 650°C
CE-compliant	Yes
Mass and weight	
Diameter	260 mm
Height (H)	60 mm
Gross weight (including packaging)	2,2 Kg
Net weight	2,2 Kg
Contents / packaging quantity	1 Piece

Rondo-Lite 260 800-830 10W ET phc | Art. No. 87626010.1061f90.000