PAD LEDTube

Moisture-proof luminaire

PAD 218 for LED Tube D | Art. No. 771218.031.001.0.00

Illustration similar

PMMA 650°C

IK05

HB

IP65

Moisture-proof luminaire with diffuser for LED tube. Short-circuit protection thanks to built-in micro-fuse. Luminaire base made of glass-fibre-reinforced polyester, light grey, flame retardant. Diffuser made of UV-resistant polymethyl methacrylate (PMMA), pearled. Stainless-steel diffuser closure. Multifunctional rapid installation with stainless-steel mounting bracket (luminaire can be clipped in). Laterally adjustable by up to 60 mm for easy alignment of the luminaire.

Type of installation and area of application
Ceiling and wall mounting for use indoors and in covered outdoor areas • Basic lighting

Technical specifications	
Art. No.	771218.031.001.0.00
Article name	PAD 218 for LED Tube D
Light source	LEDtube
Socket / base	G13 / T8 (26)
Number of light sources	2
Dimmable	not dimmable
Mains voltage	230V/50Hz
Voltage type	AC
Light optics	Diffuser made of UV-resistant polymethyl methacrylate (PMMA)
Connection type	3-pin push-fit connector with plug-in contact
Housing	Housing made of flame-retardant, glass-fibre-reinforced polyester (GRP)
Cable entry (position)	front
Testing	
Protection class	SC I
Protection grade	IP65
Information about protection grade	The protection grade is only guaranteed at the factory if mounted using the enclosed mounting bracket
Shock resistance	IK05
Flammability (UL94)	HB
Glow-wire resistance	PMMA 650°C
CE-compliant	Yes
Mass and weight	
Length (L)	675 mm
Width (B)	155 mm
Height (H)	110 mm
Information about protection grade	The protection grade is only guaranteed at the factory if mounted using the enclosed mounting bracket

PAD 218 for LED Tube D | Art. No. 771218.031.001.0.00

Mass and weight	
Gross weight (including packaging)	2,6 Kg
Net weight	2,4 Kg
Contents / packaging quantity	1 Piece
Pallet unit	150 Piece

PAD 218 for LED Tube D | Art. No. 771218.031.001.0.00

Accessories (optional)

Art. No.	Article name
44149022	TRX chain, galvanised

Art. No.	Article name
35962280	TRA KIT TRA Clip LZP +PACD 258 - 35962280

The values stated are design values. Unless otherwise stated, the values apply to an ambient temperature of 25°C. Photometric values are subject to a general tolerance of +-10%. The technical contents correspond to the status at the time of printing. Subject to changes and errors.

LTT Leuchten-Technik Tettnang
Hermannstadtstr. 1 | 88069 Tettnang
Tel: +49 7542 5304-0
info@ltt-licht.de | **www.ltt-licht.de**