



Rondo-Lite 260 800-840 10W ET phc | Art. No. 87626010.1061f80.000



PMMA  
650°C

IK06

HB



LED universal surface-mounted luminaire IP65, built-in LED modules and LED gear. Polycarbonate (PC) housing, diffuser/cover made from acrylic (PMMA), opal. Cable entry and gland for mains cable on the underside. Internal 3-pin push-fit connector. Approved for indoor or covered outdoor use, for ceiling and wall mounting (see mounting instructions).

**Technical specifications**

|  |   |
|--|---|
| Art. No.   | 87626010.1061f80.000  |
| Article name   | Rondo-Lite 260 800-840 10W ET phc                             |
| Light source   | LED, replaceable by an authorised specialist                  |
| Energy efficiency class(es) of the installed light source(s) (A-G) | Module 1: C   |
| Gear   | LED converter, replaceable by an authorised specialist        |
| Number of light sources  | 1   |
| Dimmable   | not dimmable  |
| Mains voltage  | 220-240V/50-60Hz  |
| Voltage type   | AC  |
| Max. connected load  | 10 W  |
| Output/power factor  | 0,90  |
| Luminous efficacy, max. current draw                               | 85 lm/W   |
| Luminous flux, max.  | 850 lm  |
| Flicker value (ripple)   | <= 30%  |
| Colour temperature max.  | 4000 K  |
| Colour rendering index Ra  | Ra > 80   |
| Colour tolerance (MacAdam)   | 3   |
| Life expectancy  | 50000 h   |
| Lifetime rating  | L80/B10   |
| Light optics   | Diffuser made of UV-resistant poly-methyl methacrylate (PMMA) |
| Light distribution   | Extensive   |
| Beam angle   | 120°  |

**Type of installation and area of application**

Ceiling and wall mounting  
for use indoors and in covered outdoor areas

- Basic lighting

Rondo-Lite 260 800-840 10W ET phc | Art. No. 87626010.1061f80.000

| Technical specifications                    |  |
|---|--|
| Unified Glare Rating UGR – max 4H-8H        | 25   |
| Connection type                             | 3-pin push-fit connector with plug-in contact      |
| Number of luminaires on circuit breaker B16 | 80 Piece   |
| Housing                                     | Housing made of flame-retardant polycarbonate (PC) |
| Cable entry (position)                      | rear   |
| Ambient operating temperature – min.        | -20 °C   |
| Ambient operating temperature – max.        | 25 °C  |
| Testing                                     |  |
| Protection class                            | SC I   |
| Protection grade                            | IP65   |
| Shock resistance                            | IK06   |
| Flammability (UL94)                         | HB   |
| Glow-wire resistance                        | PMMA 650°C   |
| CE-compliant                                | Yes  |
| Mass and weight                             |  |
| Diameter                                    | 260 mm   |
| Height (H)                                  | 60 mm  |
| Gross weight (including packaging)          | 2,2 Kg   |
| Net weight                                  | 2,2 Kg   |
| Contents / packaging quantity               | 1 Piece  |

Rondo-Lite 260 800-840 10W ET phc | Art. No. 87626010.1061f80.000