



Kayla 4 25-39W 3200-4700 840 ETC | Art. No. 89629-39.6524c81.400



PMMA
650°C

IK02

HB



Round, flat, wall and ceiling luminaire with LED technology. Housing made of profiled, white, powder-coated steel. Cambered, smooth cover made of UV-resistant PMMA (acrylic glass), opal. With adjustable light output (MultiLumen), pre-set to maximum output upon delivery. Practical, integrated, bayonet closure device, no separate closures necessary. 3-pin push-fit connector with plug-in contact, loop-through possible, 2 cable entries. Suitable for wall and ceiling mounting or suspended via 3-point cable suspension. Approved for indoor use.

Technical specifications

Art. No.	89629-39.6524c81.400
Article name	Kayla 4 25-39W 3200-4700 840 ETC
Light source	LED, replaceable by an authorised specialist
Energy efficiency class(es) of the installed light source(s) (A-G)	Module 1: C
Gear	LED converter, replaceable by an authorised specialist
Number of light sources	1
Dimmable	not dimmable
Mains voltage	220-240V/50-60Hz
Voltage type	AC/DC
Min. connected load	29 W
Max. connected load	39 W
Output/power factor	0,95
Luminous efficacy, min. current draw	128 lm/W
Luminous efficacy, max. current draw	121 lm/W
Luminous flux, min.	3700 lm
Luminous flux, max.	4700 lm
Flicker value (ripple)	<= 5%
Colour temperature max.	4000 K
Colour rendering index Ra	Ra > 80
Colour tolerance (MacAdam)	3
Life expectancy	50000 h
Lifetime rating	L80/B10

Type of installation and area of application

Ceiling and wall mounting, Suspended version available.
Approved for indoor use only

- Basic lighting

Kayla 4 25-39W 3200-4700 840 ETC | Art. No. 89629-39.6524c81.400

Technical specifications

Light optics	Diffuser made of UV-resistant poly-methyl methacrylate (PMMA)
Light distribution	Extensive
Beam angle	120°
Unified Glare Rating UGR – max 4H-8H	25
Connection type	3-pin push-fit connector with plug-in contact
Number of luminaires on circuit breaker B16	21 Piece
Housing	Steel housing, white
Cable entry (position)	rear
Ambient operating temperature – min.	-20 °C
Ambient operating temperature – max.	25 °C

Testing


Protection class	SC I
Protection grade	IP40
Shock resistance	IK02
Flammability (UL94)	HB
Glow-wire resistance	PMMA 650°C
CE-compliant	Yes

Mass and weight

Diameter	464 mm
Height (H)	120 mm
Gross weight (including packaging)	2,348 Kg
Net weight	2,231 Kg
Contents / packaging quantity	1 Piece

Kayla 4 25-39W 3200-4700 840 ETC | Art. No. 89629-39.6524c81.400

Accessories (optional)




Art. No.	Article name
35974070	Cable suspension



Art. No.	Article name
36055245	Deco-ring RKL 4 white



Art. No.	Article name
36055248	Deco-ring RKL 4 silver



Art. No.	Article name
45640316	Diffuser RKF-Z 4



Art. No.	Article name
89600000.000	Lamp shade

Replacement parts



Art. No.	Article name
45640326	Diffuser RKF 4