




RKL 3 AQUA 7-22W 700-2600lm 830 ET HF | Art. No. 89007-22.6541s91.351



PMMA
650°C

IK02

HB



Round LED surface-mounted luminaire with opal cover with increased protection grade, switchable via integrated HF sensor. Suitable for humid environments. With adjustable light output (MultiLumen), pre-set to maximum output upon delivery. For ceiling or wall mounting. White housing made of polycarbonate (PC) with pressure compensation plug. Domed, textured cover made of UV-resistant polymethyl methacrylate (PMMA). Also available with high-impact cover made of polycarbonate (PC). Secure and sturdy diffuser/cover attachment thanks to internal closure device. 5-pin push-fit connector with plug-in contact, loop-through possible. 2 cable entries. Approved for use indoors and in covered outdoor areas.

Type of installation and area of application

Ceiling and wall mounting
for use indoors and in covered outdoor areas

- Basic lighting

Technical specifications

Art. No.	89007-22.6541s91.351
Article name	RKL 3 AQUA 7-22W 700-2600lm 830 ET HF
Light source	LED, replaceable by an authorised specialist
Energy efficiency class(es) of the installed light source(s) (A-G)	Module 1: C
Gear	LED converter, replaceable by an authorised specialist
Number of light sources	1
Dimmable	not dimmable
Mains voltage	230V/50Hz
Voltage type	AC
Min. connected load	7 W
Max. connected load	22 W
Output/power factor	0,90
Luminous efficacy, min. current draw	100 lm/W
Luminous efficacy, max. current draw	118 lm/W
Luminous flux, min.	700 lm
Luminous flux, max.	2600 lm
Flicker value (ripple)	<= 3%
Colour temperature max.	3000 K
Colour rendering index Ra	Ra > 80
Colour tolerance (MacAdam)	3
Life expectancy	72000 h
Lifetime rating	L80/B10

RKL 3 AQUA 7-22W 700-2600lm 830 ET HF | Art. No. 89007-22.6541s91.351

Technical specifications

Light optics	Diffuser made of UV-resistant poly-methyl methacrylate (PMMA)
Light distribution	Extensive
Beam angle	120°
Unified Glare Rating UGR – max 4H–8H	22
Connection type	5-pin push-fit connector with plug-in contact
Number of luminaires on circuit breaker B16	50 Piece
Housing	Housing made of flame-retardant polycarbonate (PC)
Cable entry (position)	rear
Ambient operating temperature – min.	-25 °C
Ambient operating temperature – max.	25 °C

Testing

Protection class	SC I
Protection grade	IP65
Shock resistance	IK02
Flammability (UL94)	HB
Glow-wire resistance	PMMA 650°C
CE-compliant	Yes
D marking	Yes

Mass and weight

Diameter	375 mm
Height (H)	135 mm
Gross weight (including packaging)	1,5 Kg
Net weight	1,4 Kg
Contents / packaging quantity	1 Piece
Pallet unit	100 Piece

RKL 3 AQUA 7-22W 700-2600lm 830 ET HF | Art. No. 89007-22.6541s91.351