# RKL

Ceiling and wall luminaire


## RKL 3 2x60 E27 | Art. No. 880260.000.003.0.00



PMMA 650°C

IK02

HB




IP40

Surface-mounted luminaire for (LED) luminaire with E27 base. Round design with opal cover. Suitable for ceiling and wall mounting. Housing made of profiled, white lacquered steel. Domed, textured cover made of UV-resistant polymethyl methacrylate (PMMA). Also available with high-impact cover made of polycarbonate (PC). The cover is securely attached using spring clips. 3-pin push-fit connector with plug-in contact, loop-through possible. 2 cable entries. Approved for indoor use.

| Type of installation and area of application |
|---|
| Ceiling mounting, wall mounting, for mounting directly on the ceiling or wall<br>Approved for indoor use only<br>• Basic lighting |


| Technical specifications | |
|---|---|
| Art. No. | 880260.000.003.0.00 |
| Article name | RKL 3 2x60 E27 |
| Light source | A60 |
| Socket / base | E27 |
| Number of light sources | 2 |
| Power, illuminant (max.) | 60 W |
| Dimmable | not dimmable |
| Mains voltage | 230V/50Hz |
| Voltage type | AC |
| Luminaire efficiency | 80 % |
| Light optics | Diffuser made of UV-resistant poly-methyl methacrylate (PMMA) |
| Light distribution | Extensive |
| Beam angle | 120° |
| Connection type | 3-pin push-fit connector with plug-in contact |
| Housing | Steel housing, white |
| Cable entry (position) | rear |
| Ambient operating temperature – max. | 25 °C |
| **Testing** | |
| Protection class | SC I |
| Protection grade | IP40 |
| Shock resistance | IK02 |
| Flammability (UL94) | HB |

# RKL 3 2x60 E27 | Art. No. 880260.000.003.0.00


| | |
|---|---|
| **Testing** | |
| Glow-wire resistance | PMMA 650°C |
| CE-compliant | Yes |
| **Mass and weight** | |
| Diameter | 375 mm |
| Height (H) | 125 mm |
| Gross weight (including packaging) | 1,7 Kg |
| Net weight | 1,4 Kg |
| Contents / packaging quantity | 1 Piece |

## RKL 3 2x60 E27 | Art. No. 880260.000.003.0.00


## Accessories (optional)



| Art. No. | Article name |
|---|---|
| 36055235 | Deco-ring RKL 3 white |



| Art. No. | Article name |
|---|---|
| 36055238 | Deco-ring RKL 3 silver |



| Art. No. | Article name |
|---|---|
| 36055241 | Deco-ring RKL 3 blue |

The values stated are design values. Unless otherwise stated, the values apply to an ambient temperature of 25°C. Photometric values are subject to a general tolerance of +-10%. The technical contents correspond to the status at the time of printing. Subject to changes and errors.

**LTT Leuchten-Technik Tettnang**
Hermannstadtstr. 1 | 88069 Tettnang
Tel: +49 7542 5304-0
info@ltt-licht.de | **www.ltt-licht.de**