


RKL 3 2x60 E27 | Art. No. 880260.000.003.0.00



Surface-mounted luminaire for (LED) luminaire with E27 base. Round design with opal cover. Suitable for ceiling and wall mounting. Housing made of profiled, white lacquered steel. Domed, textured cover made of UV-resistant polymethyl methacrylate (PMMA). Also available with high-impact cover made of polycarbonate (PC). The cover is securely attached using spring clips. 3-pin push-fit connector with plug-in contact, loop-through possible. 2 cable entries. Approved for indoor use.

Type of installation and area of application

Ceiling mounting, wall mounting, for mounting directly on the ceiling or wall
 Approved for indoor use only

- Basic lighting

Technical specifications	
Art. No.	880260.000.003.0.00
Article name	RKL 3 2x60 E27
Light source	A60
Socket / base	E27
Number of light sources	2
Power, illuminant (max.)	60 W
Dimmable	not dimmable
Mains voltage	230V/50Hz
Voltage type	AC
Luminaire efficiency	80 %
Light optics	Diffuser made of UV-resistant polymethyl methacrylate (PMMA)
Light distribution	Extensive
Beam angle	120°
Connection type	3-pin push-fit connector with plug-in contact
Housing	Steel housing, white
Cable entry (position)	rear
Ambient operating temperature – max.	25 °C
Testing	
Protection class	SC I
Protection grade	IP40
Shock resistance	IK02
Flammability (UL94)	HB

RKL 3 2x60 E27 | Art. No. 880260.000.003.0.00

Testing	
Glow-wire resistance	PMMA 650°C
CE-compliant	Yes
Mass and weight	
Diameter	375 mm
Height (H)	125 mm
Gross weight (including packaging)	1,7 Kg
Net weight	1,4 Kg
Contents / packaging quantity	1 Piece

RKL 3 2x60 E27 | Art. No. 880260.000.003.0.00

Accessories (optional)



Art. No.	Article name
36055235	Deco-ring RKL 3 white

Art. No.	Article name
36055238	Deco-ring RKL 3 silver

Art. No.	Article name
36055241	Deco-ring RKL 3 blue