


Quadro-Lite 300 1100-830 9W ETC | Art. No. 87330009.1081o90.000



PMMA
650°C

IK02

HB



LED surface-mounted luminaire. Suitable for use as a house-number light (digits not included). The built-in LED modules are replaceable. White polycarbonate (PC) housing, diffuser/cover made from acrylic (PMMA), opal. Rear cable entry and gland for mains cable. Internal 3-pin push-fit connector. Approved for use indoors or in covered outdoor areas, suitable for ceiling and wall mounting.

Type of installation and area of application

Ceiling and wall mounting
for use indoors and in covered outdoor areas

- Basic lighting

Technical specifications

| | |
|--|---|
| Art. No. | 87330009.1081o90.000 |
| Article name | Quadro-Lite 300 1100-830 9W ETC |
| Light source | LED, replaceable by an authorised specialist |
| Energy efficiency class(es) of the installed light source(s) (A-G) | Module 1: C |
| Gear | LED converter, replaceable by an authorised specialist |
| Number of light sources | 1 |
| Dimmable | not dimmable |
| Mains voltage | 230V/50Hz |
| Voltage type | AC/DC |
| Max. connected load | 9 W |
| Output/power factor | 0,80 |
| Luminous efficacy, max. current draw | 122 lm/W |
| Luminous flux, max. | 1100 lm |
| Colour temperature max. | 3000 K |
| Colour rendering index Ra | Ra > 80 |
| Life expectancy | 50000 h |
| Lifetime rating | L90/B10 |
| Light optics | Diffuser made of UV-resistant poly-methyl methacrylate (PMMA) |
| Light distribution | Extensive |
| Beam angle | 120° |
| Unified Glare Rating UGR – max 4H–8H | 22 |
| Connection type | 3-pin push-fit connector with screw contact |

Quadro-Lite 300 1100-830 9W ETC | Art. No. 87330009.1081o90.000

Technical specifications

| | |
|--------------------------------------|--|
| Housing | Housing made of flame-retardant polycarbonate (PC) |
| Cable entry (position) | rear |
| Ambient operating temperature – min. | -30 °C |
| Ambient operating temperature – max. | 35 °C |

Testing

| | |
|----------------------|------------|
| Protection class | SC I |
| Protection grade | IP65 |
| Shock resistance | IK02 |
| Flammability (UL94) | HB |
| Glow-wire resistance | PMMA 650°C |
| CE-compliant | Yes |

Mass and weight

| | |
|------------------------------------|---------|
| Length (L) | 300 mm |
| Width (B) | 300 mm |
| Height (H) | 90 mm |
| Gross weight (including packaging) | 2 Kg |
| Net weight | 1,8 Kg |
| Contents / packaging quantity | 1 Piece |

Quadro-Lite 300 1100-830 9W ETC | Art. No. 87330009.1081o90.000

Accessories (optional)

01234/
56789-

| Art. No. | Article name |
|----------|---------------------------|
| 28990450 | Number set QUADRO-LITE DS |