



**RKL 6 Z 63/69/80W 840 ETC ES3** | Art. No. 88263-80.6524c81.676



PMMA  
650°C

IK02

HB



Round LED surface-mounted luminaire with emergency lighting function (single accumulator) and with adjustable light output (MultiLumen), pre-set to maximum output upon delivery. Suitable for ceiling and wall mounting. Housing made of profiled, white lacquered steel. Cylindrical, smooth cover made of UV-resistant polymethyl methacrylate (PMMA), opal. The cover is securely attached using spring clips. 5-pin push-fit connector with plug-in contact, loop-through possible. 2 cable entries.

**Technical specifications**

Art. No.	88263-80.6524c81.676
Article name	RKL 6 Z 63/69/80W 840 ETC ES3
Light source	LED, replaceable by an authorised specialist
Energy efficiency class(es) of the installed light source(s) (A-G)	Module 1: D
Gear	LED converter, replaceable by an authorised specialist
Number of light sources	1
Dimmable	not dimmable
Mains voltage	220-240V/50-60Hz
Voltage type	AC
Min. connected load	63 W
Max. connected load	80 W
Output/power factor	0,97
Luminous efficacy, min. current draw	138 lm/W
Luminous efficacy, max. current draw	136 lm/W
Luminous flux, min.	8700 lm
Luminous flux, max.	10900 lm
Luminous flux during emergency operation	290 lm
Flicker value (ripple)	<= 5%
Colour temperature max.	4000 K
Colour rendering index Ra	Ra > 80
Colour tolerance (MacAdam)	3
Life expectancy	50000 h

**Type of installation and area of application**

- Ceiling and wall mounting
- Approved for indoor use only
- Basic lighting with emergency lighting function

RKL 6 Z 63/69/80W 840 ETC ES3 | Art. No. 88263-80.6524c81.676

Technical specifications	
Lifetime rating	L80/B10
Light optics	Diffuser made of UV-resistant poly-methyl methacrylate (PMMA)
Light distribution	Extensive
Beam angle	120°
Unified Glare Rating UGR – max 4H-8H	25
Connection type	5-pin push-fit connector with plug-in contact
Number of luminaires on circuit breaker B16	30 Piece
Housing	Steel housing, white
Cable entry (position)	rear
Emergency lighting autonomy	3 h
Ambient operating temperature – min.	5 °C
Ambient operating temperature – max.	25 °C
Testing	
Protection class	SC I
Protection grade	IP40
Shock resistance	IK02
Flammability (UL94)	HB
Glow-wire resistance	PMMA 650°C
CE-compliant	Yes
Mass and weight	
Diameter	580 mm
Height (H)	110 mm
Gross weight (including packaging)	4,5 Kg
Net weight	3,6 Kg
Contents / packaging quantity	1 Piece

RKL 6 Z 63/69/80W 840 ETC ES3 | Art. No. 88263-80.6524c81.676

### Accessories (optional)



Art. No.	Article name
36055255	Deco-ring RKL 6 white



Art. No.	Article name
36055258	Deco-ring RKL 6 silver



Art. No.	Article name
36055261	Deco-ring RKL 6 blue

### Replacement parts



Art. No.	Article name
45662426	Diffuser RKL-Z 6