



Moisture-proof luminaire


EURO-FFL 236 for LED Tube, D Art. No. 800236.031.000.0.37



















Uncovered moisture-proof luminaire, IP65, protection class II, for 2xLED tube 1200 mm. Exclusively for use with ENEC/VDE certified LED tube (LED retrofit) on mains voltage 230V. Shortcircuit protection via built-in micro-fuse. Including lamp protection tube (LS) made of polycarbonate (PC) and screw rings. Housing and cover made of glass-fibre-reinforced polyester, light grey, flame retardant. Quick-release fasteners with 180° rotation. Cable entry (M20) and gland for mains cable on both end faces. Internal push-fit connector at the front. Approved for indoor or covered outdoor use, for ceiling and wall mounting (see mounting instructions).

Ceiling and wall mounting, Suspended version available., Trunking TRA for use indoors and in covered outdoor areas

• Basic lighting

Technical specifications	
Art. No.	800236.031.000.0.37
Article name	EURO-FFL 236 for LED Tube, D
Light source	LEDtube
Socket / base	G13/T8(26)
Number of light sources	2
Dimmable	not dimmable
Mains voltage	230V/50Hz
Voltage type	AC
Connection type	2-pin push-fit connector with screw contact
Housing	Housing made of flame-retardant, glass-fibre-reinforced polyester (GRP)
Cable entry (position)	front
Testing	
Testing Protection class	SC II
-	SC II IP65
Protection class	
Protection class Protection grade	IP65
Protection class Protection grade Shock resistance	IP65 IK07
Protection class Protection grade Shock resistance Flammability (UL94)	IP65 IK07 HB
Protection class Protection grade Shock resistance Flammability (UL94) Glow-wire resistance	IP65 IK07 HB GRP 850°C
Protection class Protection grade Shock resistance Flammability (UL94) Glow-wire resistance CE-compliant	IP65 IK07 HB GRP 850°C Yes
Protection class Protection grade Shock resistance Flammability (UL94) Glow-wire resistance CE-compliant D marking	IP65 IK07 HB GRP 850°C Yes
Protection class Protection grade Shock resistance Flammability (UL94) Glow-wire resistance CE-compliant D marking Mass and weight	IP65 IK07 HB GRP 850°C Yes Yes
Protection class Protection grade Shock resistance Flammability (UL94) Glow-wire resistance CE-compliant D marking Mass and weight Length (L)	IP65 IK07 HB GRP 850°C Yes Yes 1265 mm





EURO-FFL 236 for LED Tube, D | Art. No. 800236.031.000.0.37

Mass and weight	
Gross weight (including packaging)	1,8 Kg
Net weight	1,8 Kg
Contents / packaging quantity	1 Piece






EURO-FFL 236 for LED Tube, D Art. No. 800236.031.000.0.37

Accessories (optional)





Art. No.	Article name
36078004	Wire mesh protection SG 236

Art. No.	Article name
	Euro-FFL Befestigungssatz