
Quadro-Lite
Ceiling and wall luminaire

Quadro-Lite 300 1100-840 9W ETC | Art. No. 87330009.1081o80.000





PMMA 650°C
IK02
HB

IP65

LED surface-mounted luminaire. Suitable for use as a house-number light (digits not included). The built-in LED modules are replaceable. White polycarbonate (PC) housing, diffuser/cover made from acrylic (PMMA), opal. Rear cable entry and gland for mains cable. Internal 3-pin push-fit connector. Approved for use indoors or in covered outdoor areas, suitable for ceiling and wall mounting.

Type of installation and area of application
Ceiling and wall mounting for use indoors and in covered outdoor areas • Basic lighting

Technical specifications	
Art. No.	87330009.1081o80.000
Article name	Quadro-Lite 300 1100-840 9W ETC
Light source	LED, replaceable by an authorised specialist
Energy efficiency class(es) of the installed light source(s) (A–G)	Module 1: B
Gear	LED converter, replaceable by an authorised specialist
Number of light sources	1
Dimmable	not dimmable
Mains voltage	230V/50Hz
Voltage type	AC/DC
Max. connected load	9 W
Output/power factor	0,80
Luminous efficacy, max. current draw	122 lm/W
Luminous flux, max.	1100 lm
Colour temperature max.	4000 K
Colour rendering index Ra	Ra > 80
Life expectancy	50000 h
Lifetime rating	L90/B10
Light optics	Diffuser made of UV-resistant polymethyl methacrylate (PMMA)
Light distribution	Extensive
Beam angle	120°
Unified Glare Rating UGR – max 4H–8H	22
Connection type	3-pin push-fit connector with screw contact


Quadro-Lite
Ceiling and wall luminaire

Quadro-Lite 300 1100-840 9W ETC | Art. No. 87330009.1081o80.000

Technical specifications	
Housing	Housing made of flame-retardant polycarbonate (PC)
Cable entry (position)	rear
Ambient operating temperature – min.	-30 °C
Ambient operating temperature – max.	35 °C
Testing	
Protection class	SC I
Protection grade	IP65
Shock resistance	IK02
Flammability (UL94)	HB
Glow-wire resistance	PMMA 650°C
CE-compliant	Yes
Mass and weight	
Length (L)	300 mm
Width (B)	300 mm
Height (H)	90 mm
Gross weight (including packaging)	2 Kg
Net weight	1,8 Kg
Contents / packaging quantity	1 Piece

Quadro-Lite 300 1100-840 9W ETC | Art. No. 87330009.1081o80.000

Accessories (optional)



Art. No.	Article name
28990450	Number set QUADRO-LITE DS

The values stated are design values. Unless otherwise stated, the values apply to an ambient temperature of 25°C. Photometric values are subject to a general tolerance of +-10%. The technical contents correspond to the status at the time of printing. Subject to changes and errors.

LTT Leuchten-Technik Tettnang
Hermannstadtstr. 1 | 88069 Tettnang
Tel: +49 7542 5304-0
info@ltt-licht.de | **www.ltt-licht.de**